

DATASHEET

tempmate®-S2

The single-use temperature datalogger with display





MAINTechnical Specifications tempmate.®-S2 TH

Usage Type	Single-Use
Monitored Information	Temperature, Humidity, Light
Dimension [mm]	93 mm × 47 mm × 8 mm (L × W × H)
Weight [g]	30 g
Casing	ABS
Battery	CR2450 / non replaceable
Temperature Range	-30 °C to +70 °C
Temperature Accuracy	±0.3 °C für (-20 °C bis +40 °C); ±0.5 °C (other range)
Temperature Resolution	0.1 °C
T90	30 min (internal sensor)
Ambient Light Sensor	Light event detection
Humidity Range	0 - 100% RH
Humidity Accuracy	at +25 °C: ±3% RH (0 to 100% RH); ±5% (others)
Humidity Resolution	0.1% RH
Indication / Display	LED indication & Multifunctional LCD
Protection Class	IP 52
Shelf Life	Minimum 24 months*
Connection Interface	USB 2.0, A-Type
Memory Capacity (measurements)	32,000 readings
Run Time	Up to 180 days (depending on temperature range & log interval)
Logging Interval	Default: 10 min.; others on request
Startup Mode	Button, scheduled start, start through tempbase 2 Software
Stop Mode	Button or through tempbase 2 Software
Alarm Configuration	Up to 5 alarm limits customizable, single or cumulative via temp base 2 Software

OTHER SPECIFICATIONS

Temporary PDF	The PDF Report is available at anytime without stopping the Logger
Conformity	EN 12830, CE, RoHS, RTC-DO-160, MSDS
Validation Certificate	6 points (hardcopy) & PDF in memory
Reprogrammable	Yes, via tempbase 2 Software
Report Generation	Automatic PDF & CSV report
Password Protection	Optional on request
Backup-Log-Feature	Yes
Accessories incl.	Validation Certificate

* Since environmental influences can affect the lifespan of batteries, we recommend that all our products be stored in the conditions that are optimal for them. In this way, the shelf life given at the time of purchase can be guaranteed.
Optimal storage conditions: +15°C to +23°C / 45% to 75% rH.

meri.si
Najboljši v merjenju.

tel.: 040 568 887
e-pošta: info@meri.si
splet: www.meri.si



PLEASE, contact us for further questions.